







Standard equipment:

Blade guard with dust extractor connection 38 mm Saw blade diam. 250mm Riving knife Motor w/brake 1.8kW Alu. fence Workstand with folding legs (for levelling machine)

Optional equipment:

Extension table, aluminium 1m Extension table, steel 1.5m can be used on either side of machine Dust collector

Lightweight table saw for most carpentry jobs; site and workshop applications. Cross cut, Rip, Mitre and Compound Mitre cuts are easy and safe to perform. Powerful and versatile - Die Cast Aluminium table top. Easily transportable weighs only 37 kg - yet is completely stable.



A **Norsaw[®] 250** can be used on a flat, level work surface without extending the legs.



Norsaw 250 - the complete workshop machine for all woodcutting operations.





Handle positioned beneath saw table for carrying machine. Totally portable at all times.



Maximum 80mm depth of cut.



Wheels for complete manoeuverability.

Technical data:

Norsaw 250[®]

Manufacturer:	Ernex AS, Norway, NS-ISO 9001
Model:	Norsaw 250
Table size:	670 x 565mm
Height:	Collapsed: 430mm
i loight.	With stand: 860mm
Weight:	37kg
Saw blade:	Diam.: 250mm, carbide tipped Z=40
Arbor hole:	30mm
Kerf width:	3.2mm
Motor:	Universal motor w/brake
Motor.	230V/single phase 1.8kW
Spindle speed:	4.500 rpm.
Peripheral speed:	59 mps.
Fuse:	16A time-lag
Cable dim.:	Single phase 3 x 2.5 mm ²
Extension cord:	Max.: 25m
Switch:	On/off with overload and
Switch:	
Riving knife:	low-voltage cutout Hardened steel, thickness 2.5mm
0	•
Cutting depth:	90° - 80mm (vertical) 45° - 60mm (tilted)
Clide (nuch traval)	
Slide/push travel:	130mm
Cutting width:	Up to 310mm
	(Dependent on material thickness)
Tilt range (stepless):	-2° - +47°
Turntable rotation:	0-135° (+90°45°)
Noise as per	
ISO R-495:	No-load: 89db
	Loaded: 92db
CE-certification:	Certified by Dansk Teknologisk Institut, Aarhus
	ID-No. 0396. Approval certificate No.: 2004-1-0187.

Head office and factory Tistedal, Norway





Ernex AS, Bjørnstadgt. 7, N-1792 Tistedal Tel.: 69178330-Fax: 69178360 E-mail: ernex@ernex.no-www.ernex.no