

Code	Description
000689	FORTE 520
000689400	FORTE 520 CE



Thicknessing machine

Technical data

Net weight: kg 685

Useful working width mm 520.

Worktable dimensions mm 900X520

Max working height mm 300.

Min working height mm 2.

Min workpiece length mm 280.

Max. cutting depth mm 8

Cast-iron table

N° 1 idle roller on table.

N° 2 outfeed motor-driven rollers.

Complete with sound-proof material.

Table height-adjustment by 4 cylinders

Motor-driven lifting of the table with fine adjustment electric by pushbutton

Feeding speed 4 - 7 - 10.5 - 16.5 m/1'

Cutterblock diameter mm 120

4 cutters mm 520 x 30 x 3

Cutterblock rotation speed 5600 rpm

Lifting gear motor HP 0.33 (kw 0.25)

Digital read out for table positioning

Motor Hp 5,5 (kw 4)

Accessories on request

081000	Motor power hp 7,5 (kw 5,5)
085000	Motor power hp 10(kw 7,5)
258E00	Tersa planer shaft 520 mm each
259E00	Set of extra knives for tersa planer shaft 520 mm
506D00	Set of extra knives on standard shaft
084000	2° idle roller on the table
089000	Sectionated toothed roller
735E00	Rubber rollers
201D00	Electronic digital-read out
960E00	Electronic inverter for feeding speed adjustment from 3 to 25 mt/min
903D00	Electronic programmer for the automatic vertical programming of the table. Possibility to store up 99programmes. Possibility of selecting any table position in addition to 99programmes. Possibility of correcting the position value for the selected programme. Safety limit switch for the automatic lifting
IMB689	Packing in wooden case
VLT689	2% increase for voltage different from volt 400/3/50.
CSA689	Csa norms
209F00	Posizionatore elettronico qem