



CNC machining centre with edgebanding

Art. No. 9333

HOMAG BAZ 723 /58/16/V/K PROFI

Year of manufacture	2014
Working dimension X	5.860 mm
Working dimension Y	1.825 mm
Working dimension Z	300 mm
Independent Z-axes	4
Number of milling spindles	2
Main motor power	14,5 kW
Rotation speed max	24.000 rpm
Torque support	✓
4th axis	C-axis
Tool clamping system	HSK-F63
Tool changer positions	24
Vertical drilling spindles	34
Horizontal drilling spindles in X	4
Horizontal drilling spindles in Y	4
Groove saw	90° turnable
Edgebanding aggregate	Seperate Y-axis
Edgeband height max	65 mm
Places in coil magazine	2
Gantry machine	Fix gantry, moving table
Machine table	Pod and rail table
Number of consoles	12
2 tables	✓
4-field processing	✓
Self-adjusting machine table	✓
Vacuum pump	✓
Capacity vacuum pump	500 m³/h
Safety device	enclosed fence
Chip conveyor	✓
Handheld terminal	✓
Enclosed drag chain	✓
Workpiece support aids	✓
HOMAG AP table	✓
Pendulum machining	✓
Control	HOMAG POWER CONTROL
Software	HOMAG WOODWOP



CE marking



Some information was estimated due to a lack of available data, transferred from brochures or taken from third parties without verification.